



## SF (Supafix) Economical Insulated Cavity Closer

Length m	Cavity Width mm	Reference
2.1 or 3.0	50, 65, 75, 85, 90, 100	SF (cavity width/length)

## SF-Multi (Supafix) Economical Insulated Cavity Closer

2.4	to suit cavities 50-100mm	SF Multicloser
-----	---------------------------	----------------

## SFR (Supafix FIRE-RATED) Economical Insulated Cavity Closer

2.4	50, 80, 90, 100	SFR (cavity width)
SFR provides 60 mins fire integrity		

## TF1000/TF2000 Insulated Cavity Closer

2.1 or 3.0	50,75,100 (TF1000)	TF1 (cavity width/length)
2.1 or 3.0	110,125,150,160 (TF2000)	TF2 (cavity width/length)

## TF1000/TFR2000 FIRE RATED Insulated Cavity Closer

2.4	50-100	TFR1000 (cavity width/length)
2.4	110-160	TFR2000 (cavity width/length)
TFR1000 (50-100mm) provides 60 mins fire integrity, TF2000 (110-160) provides 30 mins		

## Frame Formers Insulated Cavity Closer made into Pre-formed frames

Fully insulated cavity closers made into sturdy factory built frame former eliminating the need for site fabricated timber templates around window and door reveals. For further information please contact your local Encon branch.

## Insulated DPC (Decaproof)

Reference	Length m	Size mm
DP1	2.5	165 x 100 x 18
DP2	2.5	225 x 150 x 18
DP3	10m coil	165 x 100 x 12
DP4	10m coil	225 x 150 x 12

## Dacablock Fire Rated DPC

DB5	1.2	165 x 100 x 25
DB6	1.2	225 x 150 x 25
Dacablock provides 60 mins fire integrity.		

## Dacastop Fire Rated Acoustic Party Wall Barrier

DS1/75 or 100	1.2	360 x 260 x 75/100
DS2/75 or 100	1.2	400 x 260 x 75/100
DS3/75 or 100	1.2	500 x 260 x 75/100
DS4/75 or 100	1.2	600 x 260 x 75/100
Dacastop provides 60 mins fire integrity.		

